HW93696A & HW93696U

2-1/2 Ton Air Operated End Lift

U-Model with Remote Operation

Made in USA

Three-way heavy duty brass air valve provides precision control when lifting or lowering a vehicle

Safety latch design provides five different automatic safety lock positions to prevent unintentional lowering of load

Front swivel caster wheel and two 8″ diameter rear tires

Adjustable lifting arm can be extended to desired position

HW93690

Made in USA

10 Ton Air Operated End Lift

Three-way heavy duty brass air valve provides precision control when lifting or lowering a vehicle

Safety latch design (in back) provides six different automatic safety lock positions to prevent unintentional lowering of load

Adjustable lifting arm can be extended to desired position

Two front swivel caster wheels and two 12″ diameter semi-pneumatic rear tires provide easy maneuvering

Heavy duty wide base for stability and strength

Model	Capacity	Minimum Height	Maximum Height	Power Raise	Saddle Spread	Min. Air Pressure For Rated Load	Distance (Lifting to Front of Saddle)	G.W.
HW93690	10 Ton	18-1/2″	50-1/2″	28”	28″ - 53″	200 PSI	17″	641 Lbs.
HW93696A	2-1/2 Ton	8″	35-3/8″	24-3/4	23-1/4″ - 41-1/4″		19″	210 Lbs.
HW93696U								214 Lbs.