# Orbital Pump Bottle Jacks

- Textured, heat treated saddle provides lifting area with secure grip
- Heat treated extension screw allows height adjustment and maximum lift height
- U.S. Patented by-pass device protects hydraulic system from over traveling damage
- Industrial hard chrome plated ram prevents scratching and corrosion
- A wide, rugged base provides stability and strength
- Critical stress points are reinforced in all models for added durability and dependability
- Fully serviceable design

| Capacity (tons) | Model Number | Min. Height (in) | Max. Height (in) | Extension Screw (in) | Hydraulic Lifting (in) | Base Size (L x W) (in) | Weight (lbs) |
|---|---|---|---|---|---|---|---|
| 12 | J10124 | 9.50 | 18.63 | 3.13 | 6.00 | 7.50 x 4.63 | 20.0 |
| | J10126 | 6.13 | 10.63 | 1.63 | 3.00 | | 17.0 |
| 20 | J10204 | 9.63 | 18.75 | 3.88 | 5.13 | 7.50 x 5.38 | 30.0 |
| | J10206 | 6.50 | 11.25 | 2.00 | 2.75 | | 23.0 |

# Mini Jacks

- Low Profile mini jack
- Pocket size and light weight
- Convenient for storage

| Capacity (tons) | Model Number | Min. Height (in) | Max. Height (in) | Hydraulic Lifting (in) | Base Size (L x W) (in) | Weight (lbs) |
|---|---|---|---|---|---|---|
| 5 | J11050 | 2.37 | 3.13 | 0.76 | 4.13 x 4.00 | 4.6 |
| 5 | J11055 | 3.37 | 4.88 | 1.51 | | 5.3 |
| 10 | J11100 | 4.75 | 6.25 | 1.63 | 4.88 x 4.38 | 12.5 |
| 20 | J11200 | 5.13 | 6.75 | 1.63 | 5.38 x 4.75 | 16.7 |